

# NET WORK Patch Cable

## PRODUCT DESCRIPTION

Rated temperature: 60°C, 75°C  
 Bare solid or stranded copper conductor  
 Color-coded PE insulation  
 Rip cord (optional)  
 PVC or LSZH jacket  
 Flammability grade: CMX, CM, MP, CMG  
 MPG, CMR, MPR  
 UL verified to TIA/EIA 568A/B  
 Reelex pull-out box packing available

## APPLICATION








100 Base-T4  
 100 Base-TX  
 100 VC-AnyLAN  
 1000 Base-T (Gigabit Ethernet)  
 155 Mbps ATM

## Color Code:

Pair 1: Blue, White/Blue  
 Pair 2: Orange, White/Orange  
 Pair 3: Green, White/Green  
 Pair 4: Brown, White/Brown



Construction	Conductor	Insulated Dimension mm	No. of Pairs	Shielding	Nom o.d. Mm
C5e-UTP	AWG24	0.91	4	NON	5.1
C5e-FTP	AWG24/26	1.00	4	Al-Cu	6.1
C5e-SFTP	AWG24	1.00	4	Braiding	6.6
C6-UTP	AWG24	1.02	4	NON	6.0
C6-FTP	AWG26	1.00	4	Al foil+CU	6.3
C6-SFTP	AWG26	1.00	4	Braiding	6.6
C6-SSTP	AWG27	1.00	4	Braiding	6.0



# NET WORK Patch Cord



## Ordering Information

